




**BLADDER COLOUR**

EPDM Air	Red	1   0
Butyl Air	Blue	1   1
EPDM N <sub>2</sub>	White	1   2
Butyl N <sub>2</sub>	Yellow	1   3



- In accordance to 2014/68/EU Pressure Equipment Directive and TS-EN 13831 standards
- Interchangeable bladder according to DIN 4807-3 norms, EPDM standard, Butyl optional
- Electrostatic Powder Coating
- Maximum working temperature for bladder: -10 °C – 70 °C
- Maximum temperature allowed: +110 °C (+70 °C for sanitary hot water applications)
- Suitable for Water and Water-Glycol mixtures (max. 50% glycol, Fluid group 2 according to 2014/68/EU Directives)

<b>PN</b>	<b>Art. No.</b>	<b>V (lt)</b>	<b>Dia Ø (mm)</b>	<b>H (mm)</b>	<b>h (mm)</b>	<b>C (G ISO 228-1)</b>	<b>Weight (kg)</b>	<b>Precharge (bar)</b>	<b>Std. Pack (pcs.)</b>	
10 BAR	8.00024.0210 1   0   3   0	24	280	328	180	1"	6.2	2	30 (A)	90 (B)
	8.00050.0210 1   1   3   0	50	410	454	238	1"	10.0	4	16 (A)	90 (B)
	8.00060.0210 1   2   3   0	60	410	454	238		11.0		16 (A)	40 (B)**
	8.00080.0210 1   3   3   0	80	480	518	267		15.0		8 (A)	16 (B)
	8.00100.0210 1   3   3   0	100	480	518	267		17.0		8 (A)	16 (B)

\* (Optional ¾")

\*\* Pallet size: 120x220 cm